

Approved for use through 03/31/2007. OMB 0651-0031  
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

33

Application Number

10/788,482

Filing Date

MARCH 1, 2004

First Named Inventor

MARK H. A. TIGGES

Art Unit

2628

Examiner Name

JAVID A. AMINI

Attorney Docket Number

198821-368890

### ENCLOSURES (Check all that apply)

<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input type="checkbox"/> Amendment/Reply <input type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Reply to Missing Parts/ Incomplete Application <input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____ <input type="checkbox"/> Landscape Table on CD	<input type="checkbox"/> After Allowance Communication to TC <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input type="checkbox"/> Other Enclosure(s) (please identify below):
<input type="text"/> Remarks		

### SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	MCCARTHY TETRAULT LLP (CUST. NO. 27,155)		
Signature			
Printed name	JOSEPH CONNEELY		
Date	DECEMBER 7, 2006	Reg. No.	54,883

### CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature			
Typed or printed name		Date	

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Barristers & Solicitors  
Patent & Trade-mark Agents

McCarthyTétrault



December 7, 2006

**VIA COURIER**

United States Patent and Trademark Office  
Customer Service Window, Mail Stop Amendment  
Randolph Building  
401 Dulany Street  
Alexandria, Virginia 22314  
U.S.A.

Dear Commissioner for Patents:

**RE: U.S. Patent Application No. 10/788,482**  
**Applicant: Mark H. A. Tigges**  
**For: Method and System for Inversion of Detail-In-Context Presentations**  
**Docket No.: 198821-368890**

Please find attached the following documents for filing with respect to the above patent application:

- 1.) Transmittal Form (1 sheet);
- 2.) Certified Copy of Priority Document: Canadian Patent Application No. 2,328,794; Filed December 19, 2000 (5 pages); and,
- 3.) Certified Copy of Priority Document: Canadian Patent Application No. 2,341,965; Filed March 23, 2001 (27 pages).

The Commissioner is hereby authorized to charge all necessary fees and to credit Deposit Account No. 150633 in the name of McCarthy Tétrault LLP (Customer No. 27,155).

Please date stamp and return to us the enclosed "Return Receipt Postcard".

IFW  
**McCarthy Tétrault LLP**  
Box 48, Suite 4700  
Toronto Dominion Bank Tower  
Toronto ON M5K 1E6  
Canada  
Telephone: 416 362-1812  
Facsimile: 416 868-0673  
mccarthy.ca

**Joseph Conneely**  
**Direct:** 416-601-8179  
**Direct Fax:** 416-868-0673  
**E-Mail:** jconneely@mccarthy.ca

McCarthy Tétrault

December 7, 2006

- 2 -

USPTO

Thank you very much for your assistance in this matter.

Yours very truly,  
**McCarthy Tétrault LLP**

Per:

A handwritten signature in black ink, appearing to read "J. Conneely", written over the word "Per:".

Joseph Conneely  
JC/tf  
/Enclosure



Office de la propriété  
intellectuelle  
du Canada

Un organisme  
d'Industrie Canada

Canadian  
Intellectual Property  
Office

An Agency of  
Industry Canada

*Bureau canadien  
des brevets  
Certification*

*Canadian Patent  
Office  
Certification*

La présente atteste que les documents  
ci-joints, dont la liste figure ci-dessous,  
sont des copies authentiques des docu-  
ments déposés au Bureau des brevets.

This is to certify that the documents  
attached hereto and identified below are  
true copies of the documents on file in  
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:  
**CA 2328794**, on December 19, 2000, by **ADVANCED NUMERICAL METHODS  
LTD.**, assignee of Mark H.A. Tigges, for "Computational Technique for Inversion of a  
Detail-In-Context Data Representation".

*Tracey Paulk*  
Agent certificateur/Certifying Officer

December 1, 2006

Date

CERTIFIED COPY OF  
PRIORITY DOCUMENT

Canada

(CIPO 68)  
31-03-04

OPIC



CIPO

## COMPUTATIONAL TECHNIQUE FOR INVERSION OF A DETAIL-IN-CONTEXT DATA REPRESENTATION

### 5 Introduction

Detail-in-context representations of data using techniques such as pliable surfaces<sup>1</sup> are useful in presenting large amounts of information on limited-size display surfaces. Detail-in-context views allow magnification of a particular region of interest (the “focal region”) in a data presentation while preserving visibility of the surrounding information. The ability to perform the inverse mapping from one or more points in the distorted (detail-in-context) data space back to the original undistorted original data space is of value in extending the capabilities of detail-in-context viewing to applications such as image editing. The ability to do an inverse mapping has additional important applications in the accurate positioning or repositioning by the user of one or more lenses within a given presentation space that has already been distorted. The distorted data space ultimately viewed by the user can be the end result of a series of distortion steps wherein the individual steps are not known. This document describes a computational technique for finding the inverse of a detail-in-context distortion of a data presentation. Such a presentation can be generated, using, for example, a perspective projection technique such as that described in reference 1. The basic goal can be simply stated as follows. Find, in general, the point in the undistorted data space which, when distorted, yields a specified point in the distorted data space. Then, if desired, the inverse mapping of the entire distorted space to the original undistorted data space can be obtained as the inverse mapping of the locus of the points in the distorted data space.

### Description of the Invention or Technique

The solution presented herein is an iterative method that makes use of the distortion process itself as a component of an approximation technique for computing the inverse of the distortion. Figure 1 shows a cross-section of a data presentation based on a technology known as the Elastic Presentation Space<sup>1</sup>, that uses viewer-aligned perspective projections to produce detail-in-context views in a reference view plane. In

this case, the undistorted two-dimensional data is placed in the basal plane of a three-dimensional perspective viewing volume. Points are displaced upward onto a distorted surface as shown, based on a three-dimensional "distortion function"  $D_3$ . A reference viewpoint  $V$  is defined as shown. The point  $X$  is the desired point in the distorted data space which we wish to locate in the undistorted data space. The first approximation point  $P_0$  is defined by the intersection point in the basal plane of the line through  $V$  and  $X$ . Successive approximations  $P_i$  for  $i \geq 0$  are computed as follows. First, for  $i=0$ , point  $P_0$  is displaced onto the distorted surface by application of  $D_3$ . The resultant point on the distortion function is  $P_0^D$ . The point  $P_0^D$  is projected on the line  $V-X$  as shown to locate  $P_0^P$ , the closest point to  $P_0^D$  on  $V-X$ .  $P_0^P$  is then projected onto the basal plane in the opposite direction to that of the displacement due to the distortion, to produce the next approximation  $P_1$ .  $D_3$  is applied to  $P_1$  and the process is repeated until sufficient accuracy is reached, such that  $|D_3(P_i) - X| < \delta$  where  $\delta$  is an acceptable tolerance which is application dependent. For example, an acceptable  $\delta$  could be less than half the width of a pixel for a typical display surface such as a monitor. In certain cases such as folding<sup>1</sup> (the lateral displacement of a focal region through shearing of the viewer-aligned vector defining the direction of distortion), it is possible for successive approximations for  $P_i$  to diverge, in which case a bisection of approximation points can be used to search for the desired intersection with  $V-X$ .

### Claims

- 1) Within a detail-in-context data presentation, the use of the distortion process or distortion function that produced the data presentation within an iterative technique for computing the inverse of the distortion.
- 2) The specific iterative technique using the following series of steps, to compute the inverse mapping from one or more points in a distorted (detail-in-context) data presentation back to the original undistorted original data space. Referring to figure 1, the point X is the desired point in the distorted data space which we wish to locate in the undistorted data space.
  - i) The first approximation point  $P_0$  is defined by the intersection point in the basal plane of the line through V and X.
  - ii) Point  $P_0$  is displaced onto the distorted surface by application of  $D_3$ . The resultant point on the distortion function is  $P_0^D$ .
  - iii) The point  $P_0^D$  is projected on the line V-X as shown to locate  $P_0^P$ , the closest point to  $P_0^D$  on V-X.  $P_0^P$  is then projected onto the basal plane in the opposite direction to that of the displacement due to the distortion, to produce the next approximation  $P_1$ .
  - iv) Successive approximations  $P_i$  for  $i > 1$  are then computed as follows.  $D^3$  is applied to  $P_i$ , and the process is repeated until sufficient accuracy is reached, such that  $|D_3(P_i) - X| < \delta$  where  $\delta$  is an acceptable tolerance which is application dependent.
- 3) The use of the techniques described in 1) and 2) to accurately position a new focal region in a detail-in-context data presentation.

### References Cited

1. M. S. T. Carpendale, A Framework for Elastic Presentation Space, Ph.D. Thesis, Simon Fraser University, Burnaby, BC, Canada 1992




Figure 1: An example illustrating the first iteration and the point being sought in a simple EPS of a single lens with a linear drop-off function.